



A United Rentals Company

20' HCPW Reefer Specifications



REFRIGERATION UNIT

CARRIER 69NT40-571

FEATURES

- > 3-phase 32Amp motor
- > 18m 4 pin extension lead
- > 2 x internal lights switched from inside the container
- > External emergency light and audible alarm able to be triggered internally
- > Secondary emergency alert method by brass bell in right door
- > Emergency escape hatch in right door suitable for personnel egress
- > Side wall lashing rings
- > Reverse T (flat) floor
- > 1200mm long reinforced floor at door end
- > Curtains on inside of rear door
- > 4 x floor drains
- > Forklift pockets

EXTERNAL

Length (mm)	6,058
Width (mm)	2,504
Height (mm)	2,896

DOOR OPENING

Width (mm)	2,394
Height (mm)	2,450

CARGO ACCESS

Height (mm)	2,448
-------------	-------

SUITABLE FOR HANDLING AS FOLLOWS

- > Lifting full or empty at top corner fittings by means of spreaders fitted with hooks, shackles or twist locks
- > Lifting full or empty from fork lift pockets
- > Lifting empty at two corner fittings on one side by side pick container handler
- > Lifting full or empty at bottom corner fittings using slings with terminal fittings at sling angles of 45 deg. to the horizontal plane

INTERNAL

Length (mm)	5,456
Width (mm)	2,390
Height (mm)	2,569
Cubic Capacity (m ³)	33.5

WEIGHT CAPACITIES

Max Gross Weight (kgs)	30,480
Tare Weight (kgs)	3,200
Max Pay Load (kgs)	27,280
Floor Strength (kgs)	7,260

SUITABLE FOR TRANSPORTATION AS FOLLOWS

The container is suitable for transportation in the following modes:

Road	On flat bed or skeleton chassis, secured by twistlocks or equivalent at bottom corner fittings.
Rail	On rail wagons secured by twistlock or equivalent at the bottom corner fittings.
Marine	On rail wagons secured by twistlock or equivalent at the bottom corner fittings.